

# QUESTIONS & ANSWERS

Kill your exam at first Attempt



**Huawei**

# GB0-363

*Designing Enterprise-level Networks*

**QUESTION: 83**

Which of the following should be used in the network where two equipments interconnect through multiple PPP links? ( )

- A. Multilink PPP
- B. Trunk
- C. Link Aggregation
- D. Equal-cost multi-path forwarding

**Answer: A**

**QUESTION: 84**

The maximum rate of PSTN dialing connection is ( ).

- A. 14.4Kbps
- B. 33.6Kbps
- C. 56Kbps
- D. 64Kbps

**Answer: C**

**QUESTION: 85**

The circuit simulation of ATM uses the CBR service.

- A. True
- B. False

**Answer: A**

**QUESTION: 86**

Superiority of the MSTP to the STP includes ( ).

- A. When the old root port is blocked and the designated port of the peer switch connecting to the new root port is in the Forwarding state, the root port can immediately enter the Forwarding state in the new topology.
- B. The network edge port that is directly connected to the terminal instead of connected to a bridge can directly enter the Forwarding state without any delay.
- C. A Proposal/Agreement negotiation mechanism is added between bridges.
- D. Multiple spanning tree instances can be used.

**Answer:** A, B, C, D

**QUESTION:** 87

For the sake of security and maintenance cost, which of the following should be used to provide device authentication in a large-sized and middle-sized IPsec VPN? ( )

- A. Pre-shared key
- B. Digital certificate
- C. Routing protocol authentication
- D. 802.1x

**Answer:** B

**QUESTION:** 88

Which of the following descriptions about L2TP VPN design is/are correct? ( )

- A. In the L2TP VPN, IP address can be assigned to the remote access users based on user name, and different access control policies can be deployed for these addresses on the firewall to realize multi-level control over different VPN users.
- B. In the case that the LNS uses agent authentication, the authentication will fail if the Virtual-Template interface is configured with CHAP authentication while the LAC is configured with PAP authentication.
- C. In the case that the LNS uses LCP renegotiation, it will not apply secondary authentication to the access user if no authentication is configured on the Virtual-Template interface. In this case, the user is authenticated at the LAC side only.
- D. In the case that the LNS uses LCP renegotiation, the L2TP will fail to set up the connection if no authentication is configured on the Virtual-Template interface.
- E. The combination of L2TP and IPsec can provide security encryption for VPN data.

**Answer:** A, B, C, E

**QUESTION:** 89

PIM-SM may not need RP.

- A. True
- B. False

**Answer:** B

**QUESTION:** 90

In the PIM protocol, which of the following factors should be considered first when a sender is selected by using the ASSERT mechanism? ( )

- A. Route preference
- B. Metric
- C. Route type
- D. IP address

**Answer:** A

**QUESTION:** 91

Which of the following addresses should not be aggregated? ( )

- A. Loopback address
- B. Inter-connecting address of the equipments
- C. User subnet address
- D. None of the above

**Answer:** A

For More exams visit <http://killexams.com>



[KILLEXAMS.COM](http://KILLEXAMS.COM)

*Kill your exam at First Attempt....Guaranteed!*