

QUESTIONS & ANSWERS

Kill your exam at first Attempt



HP

HP0-461

Supporting the Enterprise Virtual Array (EVA) Storage Family

D. Command View EVA reporting the shelf has unmappable hardware

Answer: D

QUESTION: 56

What happens if the mirror port connection between HSV1x0 controllers fails?

- A. There is inconsistency between the controllers.
- B. Consistency is maintained by failing all disks to one controller.
- C. Consistency is maintained by using one of the device-side loops.
- D. Consistency is maintained by using the FP1 fibre connections to the host switches.

Answer: C

QUESTION: 57

Which EVA4000/6000/8000 component is NOT a customer self repair unit?

- A. controller blower
- B. controller power supply
- C. controller cache battery
- D. Operator Control Panel

Answer: D

QUESTION: 58

In a direct connect configuration, the connection state displays "Connection failed" for an empty host port. How do you solve this problem?

- A. Remove the SFP transceiver.
- B. Insert an optical loop-back connector.
- C. Disable the host port.
- D. Interconnect the two empty host ports of the redundant controllers.

Answer: B

QUESTION: 59

EVA8000 uses active/active failover mode. A LUN is owned by controller B. Which type of access causes non-optimal performance?

- A. write I/O to controller A
- B. write I/O to controller B
- C. read I/O from controller A
- D. read I/O from controller B

Answer: C

QUESTION: 60

What is the result of pressing the bottom push-button on the EMU until it is illuminated?

- A. Error condition exists.
- B. Error conditions are viewed.
- C. Audible alarm is enabled.
- D. Audible alarm is muted or disabled.

Answer: D

QUESTION: 61

Using Command View EVA, you want to determine which controller, top or bottom, has the host port with WWID of 5000-1FE1-5002-F269. Which statement is correct?

- A. Since the WWID of the host port ends in 9, go to the Controller Properties tab for controller B and issue a Locate command.
- B. Since Controller A is always the top controller and its host ports end in C and D, the bottom controller is the one you are looking for.
- C. Since the WWID of the host port ends in 9, go to the Controller Properties tab for controller A and issue a Locate command.
- D. Since Controller B is always the bottom controller and its host ports end in C and D, the top controller is the one you are looking for.

Answer: C

QUESTION: 62

Instant Support Enterprise Edition transports error information back to HP through _____.

- A. the internet
- B. SNMP traps
- C. a paging system

D. a secure dial-up line

Answer: A



KILLEXAMS.COM

For More exams visit <http://killexams.com> -



KILLEXAMS.COM

Kill your exam at First Attempt....Guaranteed!